
## Cartridge

## 240 Wby Mag - 55 grain

## NDSLER®



Version 9.0

240 Wby	Ma	g - 55	gra	in 6m			243")	
MAXIMUM SAAMI O.A.C.L.			•	3.100"	TESTED O.A.C.L.	B.C.	S.D.	
				55gr. Spitzer	3.060"	0.288	0.133	
Due to the longer bearing surface of Ballistic Tip Lead-Free bullets, always begin with starting loads.								
			BTV	55gr. Spitzer	3.360"	0.276	0.133	
Nosler® C&D				55gr. FBSP	2.890"	0.203	0.133	
Varmageddon <sup>®</sup> VMG			VMG	55gr. FB Tipped	2.990"	0.252	0.133	
CASE TYPE:				PRIMER TYPE		Fed 2	Fed 210M	
CASE HOLDS:	S: 63.5 Gr. WATER			BARREL Length/Make		24" Li	24" Lilja	
				BARREL Twist		1-10"		
				MUZZLE VEL.			LOAD DENSITY	
ТҮРЕ	GRS.			F.P.S.	-	(VOLU	•	
H380	52.5	MAX.					87%	
	50.5		3655				84%	
	48.5		3533				80%	
H414	55.0	MAX.					90%	
	53.0		3686				87%	
	51.0		3509				84%	
IMR 4350	57.0	MAX.	3962				96%	
	55.0		3788			9	93%	
	53.0	*	3614			5	89%	
N150	52.0	MAX.	4038			9	96%	
	50.0		3891				93%	
	48.0	*	3744				89%	
IMR 4064	50.0	* MAX.	4065			8	87%	
Most Accurate	48.0		3839				84%	
Powder Tested	46.0		3612				80%	
AA 2495	49.5	MAX.	4078				89%	
	47.5		3935			8	85%	
	45.5	*	3792			5	81%	
N540	52.5	MAX.	4093				92%	
	50.5		3910			5	88%	
	48.5	*	3728			8	85%	
RL15	51.5	MAX.	4098				84%	
	49.5		3931			5	81%	
	47.5	*	3764				78%	
Big Game	54.0	MAX.	4098				87%	
	52.0	*	3969			5	84%	
	50.0		3841			5	80%	
Varget	51.5	MAX.	4105			5	88%	
	49.5	*	3934			5	84%	
	47.5		3763			5	81%	

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

\* = Most accurate load tested

\*\* = Compressed load