## Cartridge

## 240 Wby Mag - 70 grain


## Version 9.0

84%

96% 92%

89%





240 Wby	Ma	g - 70	gra	in	6mm (.243")			
MAXIMUM SAAMI O.A.C.L.				3.100"	TESTED O.A.C.L.	B.C.	S.D.	
Ballistic Tip® Varmint			BTV	70gr. Spitzer	3.060"	0.310	0.169	
Varmageddon® V			VMG	70gr. FB Tipped	3.060"	0.305	0.169	
CASE TYPE: Weatherby				PRIMER TYPE			Fed 210M	
CASE HOLDS: 61.4 Gr. WAT		TER	BARREL Length/Make		24" Lilja			
				BARREL Twist		1-10"	1	
POWDER POWDER CHG. TYPE GRS.				MUZZLE VEL. F.P.S.		LOAD (VOL	DENSITY JME)	
N150	46.0	* MAX.	3542				88%	
	44.0		3413				84%	
	42.0		3284				80%	
H4831SC	56.0	* MAX.	3589				95%	
	54.0		3447				92%	
	52.0		3304				88%	
RL19	55.0	MAX.	3642				97%	
	53.0		3479				94%	
	51.0	*	3317				90%	
H380	51.5	MAX.	3671				88%	
Most Accurate	49.5		3579				85%	
Powder Tested	47.5	*	3488		81%			
IMR 4831		* MAX.	3692				96%	
	53.0		3517				92%	
	51.0		3342				89%	
IMR 4350		* MAX.					92%	
	51.0	3543				89%		
	49.0		3368				85%	
H414		* MAX.					90%	
	51.0		3600				87%	
	49.0		3450				83%	
W760	53.0	MAX.	3751				90%	
	51.0	*	3653				87%	

3556

3701

3636

MAX. 3766

49.0

57.0

55.0

53.0

Hunter

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

<sup>&</sup>quot;Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

<sup>\* =</sup> Most accurate load tested

<sup>\*\* =</sup> Compressed load