## **Cartridge**

240 Wby Mag - 80 grain

Version 9.0





240 Wby Mag - 80 grain 6mm (.243" MAXIMUM SAAMI O.A.C.L. B.C. 3.100" TESTED O.A.C.L. S.D. Ballistic Tip® Varmint 80gr. Spitzer 3.060" 0.329 0.194 Fed 210M

**BARREL Twist** 

MUZZLE VEL.

F.P.S.

MAX. 3423

3308

3403

3275

3441

MAX. 3539

MAX. 3564

3398

3232

PRIMER TYPE Weatherby

Gr. WATER 60.1

CASE TYPE: CASE HOLDS:

**POWDER** POWDER CHG.

**TYPE** GRS.

**RL19** 54.0 52.0 50.0 \*

MAX. 3422 3252

3081

N150

Powder Tested

W760

**IMR 4350** 

43.0 \* 3193 MAX. 3528 Hunter 54.0 52.0 3468

52.0

51.0

49.0

47.0

45.0

50.0 3409

H4831SC 56.0 MAX. 3532 54.0 Most Accurate

3343 47.0 53.5 MAX. 3543 N160 51.5 3413 49.5

3282 H414 51.5 MAX. 3556 49.5 3446 47.5 3337

> 52.5 50.5

> 48.5

**IMR 4831** 54.0 MAX. 3584 52.0 3430 50.0 3277

"Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data." \* = Most accurate load tested

BARREL Length/Make







(VOLUME) 98% 94% 90%

24" Lilja 1-10"

LOAD DENSITY

92% 88% 84% 93% 89% 86%

97%

94%

90%

89%

85%

82%

99%

95%

92% 89%

86%

82%

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

<sup>\*\* =</sup> Compressed load