
Cartridge

270 Wby Mag - 100 grain

Version 9.0

NO5LER®



2/U WD	y Mag -	ruu gi	alli
MLIMIXAM	SAAMI O.A	.C.L.	3 295"

270 Cal. (.277")

MAXIMOM SAAMI O.A.C.L.			3.293		ILSIL	D O.A.C.L.	υ.	.С.	J.D.	
AccuBond® AB		100gr. Spitzer 3.200"			0.	323	0.186			
CASE TYPE:	Nosler		PRIMER TYPE				WLRM			
CASE HOLDS:	83.1 Gr. WATER		BARREL Length/Make				26" Lilja			
				BARREL Twist				1-10"		
POWDER POWDER CHG.			MUZZLE VEL.				LOAD DENSITY			
TYPE	GRS.			F.P.S.					(VOL	UME)
IMR 7828 SSC	76.0	MAX.	3600							94%
	74.0		3480							92%
	72.0	*	3359							89%
MAGPRO	80.5	MAX.	3639						•	100%
	78.5		3574							97%
	76.5	*	3508							95%
H4831SC	76.5	* MAX.	3649							96%
	74.5		3558							93%
	72.5		3466							91%
RL22	76.5	MAX.	3728							100%
Most Accurate	74.5		3576							97%
Powder Tested	72.5		3424							95%

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary *Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the

condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

^{* =} Most accurate load tested

^{** =} Compressed load