## Cartridge

## 270 Win - 100 grain

## Version 9.0

| <b>NDSLER</b><br>270 Win - 100 grain<br><b>NDSLER</b><br>270 Cal. (.277") |                   |        |              |                       |                |       |                          |       |
|---|-------------------|--------|--------------|-----------------------|----------------|-------|--------------------------|-------|
| MAXIMUM S   |                   |        |              | 3.340"                | TESTED O.A.C.L |       | .C.                      | S.D.  |
| AccuBond®   |                   |        | AB           | 100gr. Spitzer        | 3.275"         | 0     | .323                     | 0.186 |
| CASE TYPE: Nosler   |                   |        | PRIMER TYPE  |                       |                | WLR   |                          |       |
| CASE HOLDS: 64.7 Gr. WATER  |                   |        | ER           | BARREL Length/Make    |                |       | 26" Pac-Nor              |       |
|   |                   |        | BARREL Twist |                       |                | 1-10" |                          |       |
| POWDER<br>TYPE  |                   |        |              | MUZZLE VEL.<br>F.P.S. |                |       | LOAD DENSITY<br>(VOLUME) |       |
| RL15  | 54.0              | MAX.   | 3450         |                       |                |       |                          | 87%   |
| Most Accurate   | 52.0 <sup>•</sup> |        | 3324         |                       |                |       |                          | 84%   |
| Powder Tested   | 50.0              |        | 3197         |                       |                |       |                          | 80%   |
| Varget  | 54.0              | MAX.   | 3485         |                       |                |       |                          | 90%   |
|   | 52.0              |        | 3372         |                       |                |       |                          | 87%   |
|   | 50.0 *            | ÷      | 3260         |                       |                |       |                          | 84%   |
| IMR 4350  | 60.5 *            | • MAX. | 3540         |                       |                |       |                          | 00%   |
|   | 58.5              |        | 3396         |                       |                |       |                          | 97%   |
|   | 56.5              |        | 3251         |                       |                |       |                          | 93%   |
| W760  | 58.0              | MAX.   | 3554         |                       |                |       |                          | 94%   |
|   | 56.0 *            | ÷      | 3448         |                       |                |       |                          | 91%   |
|   | 54.0              |        | 3343         |                       |                |       |                          | 87%   |

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In o event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

\* = Most accurate load tested

\*\* = Compressed load