
## **Cartridge**

270 Win - 160 grain

Version 9.0





## 270 Win - 160 grain MAXIMIIM SAAMI O A C I

270 Cal. (.277"

	-•
Partition®	

160gr. Semi-Spitzer

3.340"

F.P.S.

TESTED O.A.C.L. 3.320"

B.C. 0.434

S.D. 0.298

PT CASE TYPE: Nosler

1-10"

CASE HOLDS: 63.8

PRIMER TYPE BARREL Length/Make **BARREL Twist** MUZZLE VEL.

Fed 210 24" Shlien

**LOAD DENSITY** 

85%

82%

79%

95%

92%

88%

91%

88%

84%

85%

82%

79%

91%

87%

84%

89%

86%

82%

97%

94%

90%

87%

84%

80%

95% 92%

89%

(VOLUME)

Gr. WATER POWDER CHG.

GRS.

\* MAX. 2672 H4350 51.5

49.5

**POWDER TYPE** 

47.5 **IMR 7828** 57.0

2557 2442 55.0

\* MAX. 2732 2637 53.0

2542 **RL19** 53.5 \* MAX. 2750 Most Accurate 51.5 2620 Powder Tested 49.5 2490 **IMR 4350** 51.0 MAX. 2758

49.0 2643 47.0 2528 MAX. 2761 N165 52.0 2687

50.0 48.0 2613 \* MAX. 2775 H4831SC 54.5 52.5 2683

50.5 2591 MAX. 2789 **MAGPRO** 60.0 58.0 2681 56.0 2573 **IMR 4831** 52.0 \* MAX. 2820

50.0

48.0

54.0

2722

2624

2703

56.0 \* MAX. 2828

52.0 All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary \* Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

RL22

\* = Most accurate load tested \*\* = Compressed load