Cartridge


300 Wby Mag - 190 grain

Version 9.0

96%

N D S L E R[®]

300 Wby Mag - 190 grain



MAXIMUM S	AAMI	O.A.C.L		3.560"	TESTED O.A.C.L.	B.C.	S.D.	
AccuBond® Long Range			ABLR	190gr. Spitzer	3.550"	0.597	0.286	
Custom Competition® CC				190gr. HPBT	3.550"	0.530	0.286	
CASE TYPE: Nosler				PRIMER TYPE		WLRI	WLRM	
CASE HOLDS:	92.8 Gr. WATER		BARREL Length/Make		26" P	26" Pac-Nor		
				BARREL Twist			1-10"	
POWDER TYPE	POWDER CHG. GRS.			MUZZLE VEL. F.P.S.			LOAD DENSITY (VOLUME)	
IMR 4831	75.0	MAX.	2956				86%	
	73.0		2869				84%	
	71.0	*	2782				82%	
N165	80.5	MAX.	2996				96%	
Most Accurate	78.5		2923				94%	
Powder Tested	76.5	*	2850				92%	
RL22	79.0	MAX.	3043				93%	
	77.0		2962				90%	
	75.0	*	2880				88%	
IMR 4350	75.0	MAX.	3083				86%	
	73.0		3023				84%	
	71.0	*	2963				82%	
Hybrid 100V	75.0	MAX.	3109				83%	
	73.0		3037				81%	
	71.0	*	2966				79%	
IMR 7828 SSC	83.0	* MAX.	3134				92%	
	81.0		3044				90%	
	79.0		2954				88%	
H1000	88.0	MAX.	3153			1	100%	
	86.0		3084				98%	

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary *Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the

3015

84.0

condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

^{* =} Most accurate load tested

^{** =} Compressed load