

CARTRIDGE

416 Weatherby Magnum - 400 grain

Version 8.0





416 Weatherby Mag - 400 grain

MAXIMUM S.A.A.M.I. O.A.C.L. 3.750"

416 Cal. (.416")

109%

107%

TESTED O.A.C.L. B.C. S.D.

Partition®		400gr. Spitzer	3.700"	0.390	0.330	
Solid™		400gr. Solid	3.700"	0.289	0.330	
CASE TYPE:	Weatherby	PRIMER TYPE		Fed 215	Fed 215	
CASE HOLDS:	114.5 Gr. WATER	BARREL Length/Make		26" We	26" Weatherby	
		BARREL Twist		1-14"	1-14"	
POWDER	POWDER CHG.	MUZZLE VEL.		LOAD D	ENSITY	
TYPE	GRS.	F.P.S.		(VOLUM	IE)	
H4831SC	113.0 * MAX. 2667			** 10	3%	
	111.0 2630			** 10	1%	
	109.0 2599			9	9%	
RL19	115.0 MAX. 2696			** 10	19%	
	113.0 * 2641			** 10	7%	
	111.0 2601			** 10	5%	
IMR 7828	117.0 MAX. 2704			** 10	19%	
Most Accurate	115.0 * 2667			** 10	17%	
Powder Tested	113.0 2640			** 10	5%	
RL22	117.0 MAX. 272 5			** 11	1%	

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, inc. be liable for any damages resulting from the use of this data."

2679

2607

115.0

113.0 *

^{* =} Most accurate load tested

^{** =} Compressed load