Cartridge

7mm Rem Mag - 185 grain

Version 9.0

95%

92%

89%





7 min Kem Mag - 103 gram 7 min (.2								
MAXIMUM S	AAMI	O.A.C.L	•	3.290"	TESTED O.A.C.L.	B.C.	S.D.	
Reduced Drag Factor™ RDF			RDF	185gr. HPBT	3.290"	0.719	0.328	
CASE TYPE: Nosler				PRIMER TYPE		WLR	WLRM	
CASE HOLDS: 76.6 Gr. WATER			ER	BARREL Length/Make		26" V	26" Wiseman	
				BARREL Twist		1-9"	1-9"	
POWDER TYPE	POWDER CHG. GRS.			MUZZLE VEL. F.P.S.			LOAD DENSITY (VOLUME)	
IMR 4350	56.5	* MAX.	2614				79%	
	54.5		2538				76%	
	52.5		2463				73%	
IMR 7828 SSC	60.0	MAX.	2659				81%	
	58.0	*	2578				78%	
	56.0		2496				75%	
N165	62.5	MAX.	2666				91%	
	60.5	*	2598				88%	
	58.5		2530				85%	
Norma MRP	63.0	* MAX.	2712				90%	
	61.0		2636				88%	
	59.0		2560				85%	
RL22	61.0	MAX.	2716				87%	
Most Accurate	59.0		2638				84%	
Powder Tested	57.0		2561				81%	
H1000	65.5	MAX.	2721				90%	
	63.5	*	2646				88%	
	61.5		2570				85%	
RL19	63.0	MAX.	2755				89%	
	61.0	*	2681				87%	
	59.0		2607				84%	
MAGPRO	69.0	* MAX.	2796				93%	
	67.0		2725				90%	
	65.0		2653				87%	

2639

MAX. 2800 2720

71.5

67.5

69.5 *

Magnum

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

[&]quot;Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

^{* =} Most accurate load tested

^{** =} Compressed load