
## Cartridge

## 7mm Wby Mag - 160 grain

## NOSLER®



Version 9.0

## 7mm Wby Mag - 160 grain 7mm (.284") MAXIMUM SAAMI O.A.C.L. TESTED O.A.C.L. B.C. 3.360" S.D. AccuBond<sup>®</sup> AB 160gr. Spitzer 3.360" 0.531 0.283 PT Partition<sup>®</sup> 160gr. Spitzer 3.360" 0.475 0.283 CASE TYPE: Norma PRIMER TYPE Rem 9 1/2M CASE HOLDS: Gr. WATER BARREL Length/Make 24" Lilia 81.0 BARREL Twist 1-9" POWDER POWDER CHG. MUZZLE VEL. LOAD DENSITY TYPE GRS. F.P.S. (VOLUME) H1000 75.5 MAX. 2922 99% 73.5 96% 2817 71.5 \* 2712 93% IMR 4350 64.0 MAX. 3028 85% 62.0 2943 82% 60.0 \* 2858 79% **IMR 7828** 73.0 MAX. 3040 96% 71.0 2920 93% 69.0 \* 2800 91% **RL22** 68.5 MAX. 3050 92% 66.5 2964 89% 64.5 \* 2878 87% IMR 4831 66.0 \* MAX. 3080 87% 64.0 2980 85% 62.0 2880 82% MAX. 3103 N560 69.5 95% 93% 67.5 3026 65.5 2949 90% H4831SC 70.5 MAX. 3109 91% 68.5 3038 88% 66.5 \* 2967 86% Magnum 79.5 MAX. 3110 100% 77.5 3039 97% 75.5 2969 95% Retumbo 79.5 MAX. 3192 \*\* 106% 77.5 \* 3124 103% 75.5 3056 100% **RL25** MAX. 3196 102% 76.0 74.0 3119 99% Most Accurate 97% Powder Tested 72.0 3043

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary <sup>a</sup> Because Nosler, inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In on event shall Nosler, inc. be liable for any damages resulting from the use of this data.

\* = Most accurate load tested

\*\* = Compressed load