

# **CARTRIDGE**

#### 8mm-06 - 200 grain

#### Version 8.0





## 8mm-06 - 200 grain

### 8mm (.323")

MAXIMUM C	J.A.C.	L. 3.25	0				В	.C.	S.D.
AccuBond®				200gr. Spitzer			0.	450	0.274
Custom Competition®				200gr. HPBT			0.	520	0.274
Partition <sup>®</sup>				200gr. Spitzer			0.	426	0.274
CASE TYPE:	Winchester (30-06)			PRIMER TYPE			Fed 210M		
CASE HOLDS:	60.7 Gr. WATER			BARREL Length/Make			24" Wiseman		
				BARREL Twist				1-10"	
POWDER	POWDER CHG.			MUZZLE VEL.			LOAD DENSITY		
TYPE	GRS.			F.P.S.				(VOLUI	ME)
RL19	56.5	* MAX.	2571				**	1	01%
Most Accurate	54.5		2469					9	98%
Powder Tested	52.5		2364					9	94%
H4831SC	59.0	* MAX.	2602				**	1	01%
	57.0		2518					9	98%
	55.0		2414					9	94%
IMR 4350	55.5	MAX.	2628					9	97%
	53.5	*	2502					9	93%
	51.5		2426					9	90%

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

<sup>\* =</sup> Most accurate load tested

<sup>\*\* =</sup> Compressed load