## Cartridge

300 PRC - 220 grain

Version 9.0

S.D.

0.331

104%

101%



3.700" gr. HPBT



300 PRC - 220 grai	n
<b>MAXIMUM SAAMI O.A.C.L</b>	
Custom Competition®	ſ

30 Cal. (.308")

B.C.

0.690

TESTED O.A.C.L.

3.545"

Partition®		PT	gr. Semi-Spitzer	3.540"	0	.351	0.331
CASE TYPE:	Hornady		PRIMER TYPE			WLRM	
CASE HOLDS:	87.0 Gr. WA	TER	BARREL Length/I	Иake		24" Shilen	
			BARREL Twist			1-8.5"	
POWDER	POWDER CHG.		MUZZLE VEL.			LOAD DENSITY	
TYPE	GRS.		F.P.S.			(VOLU	JME)
IMR 7828 SSC	68.5 * MAX.	2744				8	31%
	66.5	2666				7	79%
	64.5	2589				7	76%
IMR 8133	79.5 MAX.	2839			××	101%	
	77.5	2761				9	98%
	75.5 *	2684				ç	96%
RL25	78.0 MAX.	2850				9	97%
Most Accurate	76.0	2769				9	95%
Powder Tested	74.0 *	2688				9	92%
RL26	75.0 MAX.	2855				8	38%
	73.0	2772				8	36%
	71.0 *	2688				3	33%
MAGNUM	79.5 * MAX.	2860				Ğ	93%
	77.5	2783				ç	90%
	75.5	2706				3	38%
LRT	86.0 MAX.	2864				g	98%
	84.0 *	2808				ç	96%
	82.0	2752				9	94%
H1000	79.0 MAX.	2875				ç	96%
	77.0	2790				9	94%
	75.0 *	2706				ç	91%
MAGPRO	80.0 MAX.	2894				9	95%
	78.0	2823				g	92%
	76.0 *	2753				ç	90%
US869	90.0 MAX.	2914			××	1	06%

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary \* Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the

2861

2808

88.0 86.0

condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

<sup>\* =</sup> Most accurate load tested

<sup>\*\* =</sup> Compressed load