

Cartridge

204 Ruger - 40 grain

Version 9.0

NOSLER®



204 Ruger - 40 grain

20 Cal. (.204")

MAXIMUM SAAMI O.A.C.L.		2.260"		TESTED O.A.C.L.	B.C.	S.D.
Ballistic Tip® Varmint		BTV	40gr. Spitzer	2.250"	0.239	0.137
CASE TYPE:	Nosler		PRIMER TYPE	Fed 205M		
CASE HOLDS:	29.9	Gr. WATER	BARREL Length/Make	26" Pac-Nor		
			BARREL Twist	1-12"		
POWDER TYPE	POWDER CHG. GRS.		MUZZLE VEL. F.P.S.	LOAD DENSITY (VOLUME)		
AA 2015	24.0	MAX.	3484	91%		
	23.0		3354	87%		
	22.0	*	3225	84%		
IMR 4895	27.0	MAX.	3544	98%		
	26.0	*	3447	95%		
	25.0		3351	91%		
RL 10x	23.5	MAX.	3548	88%		
	22.5	*	3435	85%		
	21.5		3323	81%		
H335	25.0	MAX.	3567	85%		
	24.0		3440	81%		
	23.0	*	3313	78%		
H322 Most Accurate Powder Tested	24.5	MAX.	3608	89%		
	23.5		3474	85%		
	22.5	*	3340	81%		
Varget	27.5	MAX.	3648	99%		
	26.5	*	3527	96%		
	25.5		3407	92%		
Benchmark	26.0	MAX.	3667	94%		
	25.0		3522	90%		
	24.0	*	3377	87%		
W748	27.5	MAX.	3674	96%		
	26.5	*	3537	92%		
	25.5		3400	89%		
PP Varmint	28.0	MAX.	3728	95%		
	27.0		3584	91%		
	26.0	*	3441	88%		
CFE 223	29.5	MAX.	3815	99%		
	28.5		3643	95%		
	27.5	*	3471	92%		

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

* Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.*

* = Most accurate load tested

** = Compressed load