
Cartridge

257 Ack Imp - 110 grain

Version 9.0





25 Cal. (.257" 257 Ack Imp - 110 grain MAXIMUM O.A.C.L. B.C. 2.780" TESTED O.A.C.L. S.D. AB gr. Spitzer AccuBond® 2.780" 0.418 0.238

CASE TYPE: Nosler CASE HOLDS: 56.0

Gr. WATER

PRIMER TYPE

BARREL Twist

BARREL Length/Make

1-10" **LOAD DENSITY**

Fed 210 24" Wiseman

77%

73%

85%

81%

78%

92%

88% 84%

91% 87%

83%

94%

90%

86%

89%

86%

82%

96%

92%

88% 96%

92%

88%

99%

95% 91%

(VOLUME) 80%

POWDER POWDER CHG. MUZZLE VEL. **TYPE** GRS. F.P.S. **Big Game** 44.0 MAX. 2962 42.0 2855 40.0 * 2748 MAX. 2980 W760 45.5 43.5 2893 41.5 2807 MAX. 3000 **IMR 4831** 48.0 46.0 2883 44.0 2766 **IMR 4350**

47.5 MAX. 3013 45.5 2905 43.5 2798 47.5 MAX. 3014 N160 45.5 2888 43.5 2763 48.5 * MAX. 3031

Hunter 46.5 2943 44.5 2855 H4831SC 51.5 MAX. 3043 49.5 2953 Most Accurate Powder Tested 47.5 2863 **RL19** * MAX. 3044 49.5

47.5

45.5

51.0

49.0

47.0

2933

2822

2966

2868

MAX. 3063

RL22

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary * Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

^{* =} Most accurate load tested ** = Compressed load