Cartridge

270 WSM - 100 grain

		<u> </u>	-						
NC				R	.535 		.860	538 0.31	
270 WSM - 100 grain 270 Cal. (.277")									
MAXIMUM SAAMI O.A.C.L.				2.860"		TESTED O.A.C.	L. B	s.C.	S.D.
AccuBond® AB				100gr. Sp	itzer	2.760	0	.323	0.186
CASE TYPE:	Nosler			PRIMER TYPE				WLRM	
CASE HOLDS:	LDS: 75.1 Gr. WATER			BARREL Length/Make				26" Pac-Nor	
				BARREL Twist				1-10"	
POWDER TYPE	POWDER CHG. GRS.			MUZZLE VEL. F.P.S.				LOAD DENSITY (VOLUME)	
H4831SC	71.0 MA	MAX.	3636					9	98%
	69.0		3549					9	96%
	67.0	*	3462					9	93%
W760	65.0	MAX.	3682					9	91%
	63.0		3614					8	38%
	61.0	*	3547					8	35%
RL15	61.0	MAX.	3721					8	35%
	59.0		3660					8	32%
	57.0	*	3599						79%

68.0 MAX. 3754 97% **IMR 4350** 66.0 3641 Most Accurate 94% Powder Tested 64.0 3529 91%

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

* = Most accurate load tested

** = Compressed load