
Cartridge

270 WSM - 110 grain

Version 9.0

270 Cal. (.277")

ΝΟ	SL	



270 WSM - 110 grain

									· · /
AAMI	O.A.C.L	•	2.860"	TE	STED C	D.A.C.L.	B	.C.	S.D.
AccuBond® AB			110gr. Spitze	r 2.7	2.760" 0		0	.370	0.205
SE TYPE: Nosler			PRIMER TYPE				WLRM		
74.5 Gr. WATER			BARREL Length/Make				24" Wiseman		
			BARREL Twist					1-10"	
POWDER POWDER CHG.		MUZZLE VEL.					LOAD DENSITY		
GRS.			F.P.S.					(VOLL	JME)
73.0	MAX.	3478					**	1	04%
71.0		3376					**	1	01%
69.0	*	3274						9	98%
67.0	MAX.	3543						ç	94%
65.0		3446						9	91%
63.0	*	3350						8	38%
62.0	MAX.	3557						8	38%
60.0		3462						8	35%
58.0	*	3366						8	32%
68.0	MAX.	3630						9	99%
66.0		3523						9	96%
64.0	*	3416						ç	93%
	PowD 74.5 POWD GRS. 73.0 71.0 69.0 67.0 63.0 62.0 68.0 68.0 66.0	PowDER CHG. 73.0 MAX. 71.0 69.0 67.0 MAX. 65.0 63.0 68.0 MAX. 66.0 MAX.	AAMI O.A.C.L. AB Nosler 74.5 Gr. WATER POWDER CHG. GRS. 73.0 MAX. 3478 71.0 3376 69.0 * 3274 67.0 MAX. 3543 65.0 3446 63.0 * 3350 62.0 MAX. 3557 60.0 3462 58.0 * 3366 68.0 MAX. 3630 66.0 3523	AAMI O.A.C.L. 2.860" AB 110gr. Spitze Nosler PRIMER TYPE 74.5 Gr. WATER BARREL Lengt BARREL Twist MUZZLE VEL. GRS. MAX. 3478 73.0 MAX. 3478 71.0 3376 69.0 * 67.0 MAX. 3543 65.0 3446 63.0 * 62.0 MAX. 3557 60.0 3462 58.0 * 68.0 MAX. 3630 66.0 3523	AB 110gr. Spitzer 2.7 Nosler PRIMER TYPE 2.7 74.5 Gr. WATER BARREL Length/Make BARREL Twist BARREL Twist BARREL Twist POWDER CHG. MUZZLE VEL. F.P.S. 73.0 MAX. 3478	AAMI O.A.C.L. 2.860" TESTED C AB 110gr. Spitzer 2.760" Nosler PRIMER TYPE 2.760" 74.5 Gr. WATER BARREL Length/Make BARREL Twist BARREL Twist POWDER CHG. MUZZLE VEL. GRS. F.P.S. 73.0 MAX. 3478 71.0 3376 69.0 * 3274 67.0 MAX. 3543 65.0 3446 63.0 * 3350 62.0 MAX. 3557 63.0 * 3366 68.0 MAX. 3630 66.0 3523	AAMI O.A.C.L. 2.860" TESTED O.A.C.L. AB 110gr. Spitzer 2.760" Nosler PRIMER TYPE 2.760" 74.5 Gr. WATER BARREL Length/Make BARREL Twist BARREL Twist POWDER CHG. MUZZLE VEL. GRS. F.P.S. 73.0 MAX. 3478 71.0 3376 69.0 * 3274 67.0 MAX. 3543 65.0 3446 63.0 * 3350 62.0 MAX. 3557 63.0 * 3366 64.0 3462 65.0 3462 66.0 3523	AAMI O.A.C.L. 2.860" TESTED O.A.C.L. B AB 110gr. Spitzer 2.760" 0 Nosler PRIMER TYPE 2.760" 0 74.5 Gr. WATER BARREL Length/Make BARREL Twist POWDER CHG. MUZZLE VEL. F.P.S. *** 73.0 MAX. 3478 *** *** 71.0 3376 *** *** 69.0 * 3274 *** 67.0 MAX. 3543 *** *** 65.0 3446 *** *** 62.0 MAX. 3557 *** 68.0 MAX. 3630 *** 68.0 MAX. 3630 ***	AAMI O.A.C.L. 2.860" TESTED O.A.C.L. B.C. AB 110gr. Spitzer 2.760" 0.370 Nosler PRIMER TYPE WLRM 74.5 Gr. WATER BARREL Length/Make 24" W BARREL Twist 1-10" POWDER CHG. MUZZLE VEL. LOAD GRS. F.P.S. (VOLU 73.0 MAX. 3478 *** 1 69.0 3274

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In on event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

* = Most accurate load tested

** = Compressed load