
Cartridge

270 WSM - 160 grain

Version 9.0

270 Cal. (.277")

NOSLER®



270 WSM - 160 grain

MAXIMUM SAAMI O.A.C.L.				2.860"	TESTED O.A.C.L.	E	3.C.	S.D.
Partition®			PT	160gr. Semi-Spitzer	2.850"	C).434	0.298
CASE TYPE: Nosler			PRIMER TYPE		WLRM			
CASE HOLDS:	72.9 Gr. WATER		BARREL Length/Make		24" Wiseman			
			BARREL Twist			1-10"		
POWDER POWDER CHG.			MUZZLE VEL.		LOAD DENSITY			
ТҮРЕ	GRS.			F.P.S.			(VOLL	JME)
IMR 4350	57.0	MAX.	2895					34%
	55.0	*	2812				8	31%
	53.0		2728				_	78%
H4831SC	60.0	MAX.	2929				8	36%
	58.0		2855				8	33%
	56.0 * 27		2781				8	30%
H1000	63.0	* MAX.	2960				9	91%
	61.0		2871				8	39%
	59.0		2781				8	36%
Magnum	67.0	MAX.	2971				93%	
	65.0		2877				9	91%
	63.0	*	2783				8	38%
RL19	60.5	* MAX.	2983				90%	
Most Accurate	58.5		2889				8	37%
Powder Tested	56.5		2794				8	34%
IMR 7828	61.5	MAX.	3046			9	90%	
	59.5		2956				8	37%
	57.5	*	2865				8	34%
MAGPRO	PRO 67.5 MAX. 3082				9	95%		
	65.5		3009				9	93%
	63.5	*	2935				ç	90%
RL22	61.5	MAX.	3088				9	92%
	59.5	*	2987				8	39%
	57.5		2887				8	36%
N170	68.0	MAX.	3108			**	• 1	04%
	66.0		3017			**	• 1	01%
	64.0	*	2927				9	98%

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

* = Most accurate load tested

** = Compressed load