
Cartridge

AccuRond®

30-378 Wby Mag - 125 grain

Version 9.0

NOSLER



3 630"

30-378 wby mag - 1	125 grair
ΜΑΧΙΜΙΙΜ ΚΑΑΜΙ Ο Α C Ι	3 648"

30 Cal. (.308")TESTED O.A.C.L. B.C. S.D.

0 188

97%

95%

0.366

ACCUDONG		A D	123gi. spitzei	3.030	U	.500	0.100
Ballistic Tip®		BT	125gr. Spitzer	3.630"	0	0.366 0.188	
CASE TYPE:	Nosler		PRIMER TYPE			Fed 215	
CASE HOLDS:	127.7 Gr. WA	TER	BARREL Length/Make			26" Lilja	
			BARREL Twist		1-10"		
POWDER	POWDER CHG.		MUZZLE VEL.		LOAD DENSITY		
TYPE	GRS.		F.P.S.			(VOLUME)	
H4831SC	109.0 MAX.	3797					89%
Most Accurate	107.0	3725					87%
Powder Tested	105.0 *	3652					86%
H1000	120.0 MAX.	3807					99%
	118.0	3754					98%
	116.0 *	3701					96%
IMR 7828	109.0 MAX.	3823					91%
	107.0 *	3752					89%
	105.0	3680					87%
N165	113.0 MAX.	3828					98%

AR 125ar Spitzer

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the

3741

3654

111.0 *

109.0

condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.

^{* =} Most accurate load tested

^{** =} Compressed load