## **Cartridge**

30-378 Wby Mag - 200 grain

Version 9.0





or or only mag		
<b>MAXIMUM SAAMI O.A.C.L</b>	. 3.648"	TESTED (
A = = . D = = = d ®	AD 200ar Coit-	2 (20"

MAX. 3064

MAX. 3068

MAX. 3068

MAX. 3102

MAX. 3121

MAX. 3140

2977

2890

3014

2959

3017

2965

3047

2993

3042

2963

3068

2997

30 Cal. (.308" S.D.


MAXIMUM SAAMI O.A.C.L	3.648"		
AccuBond®	AB	200gr. Sp	
Partition®	PT	200gr. Sp	


MAXIMUM SAAMI O.A.C.L	••	3.648"	TESTED O.A.C.L.	B.C.	
AccuBond®	AB	200gr. Spitzer	3.630"	0.588	
Partition®	PT	200gr. Spitzer	3.630"	0.481	
ASE TYPE: Nosler		PRIMER TYPE		Fed 2	1

, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
Partition®			PT	200gr. Sp
CASE TYPE:	Nosler	•		PRIMER TY
CASE HOLDS:	120.8	Gr. WAT	ER	BARREL Le
				DADDEL TO

uBond®			AB	200gr. Spitzer	3.630"	0.5	588	0.301	
ition®			PT	200gr. Spitzer	3.630"	0.4	481	0.301	
E TYPE:	Nosler			PRIMER TYPE			Fed 2	15	
E HOLDS:	120.8	Gr. WA7	ER	BARREL Length/	Иake		26" Lil	ja	
				DADDEL Toules			1 10"		

POWDER TYPE	POWDER CHG. GRS.
RL22	85.5 * MAX. 2965
	83.5 2910
	81.5 2854
N165	88.0 MAX. 2972
	86.0 2905
	84.0 * 2838





80.0	
84.0	*
99.0	
97.0	*
95.0	
99.0	
97.0	

95.0 \*

112.0

110.0

94.0 92.0

108.0 \*

90.0 \*

94.0 \*

96.0

92.0

95.0

91.0

93.0 \*

RL33

H1000

**H50BMG** 

Most Accurate

Powder Tested

**IMR 7828** 

Retumbo



7 9 70
77%
84%
82%
80%
87%
85%
83%
96%
94%
93%
83%
81%

79%

85%

84%

82%

85%

84%

82%

79%

RL2

All callinge measurements are SAAWTMAXIMUM and due to variations from manufacturers actual measurements may var
"Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the
condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.
In no event shall No sler, Inc. be liable for any damages resulting from the use of this data."

<sup>\* =</sup> Most accurate load tested

<sup>\*\* =</sup> Compressed load