
Cartridge

300 RCM - 190 grain

Version 9.0

N05LER®



300 RCM - 190 grain

30 Cal. (.308")TESTED O.A.C.L. B.C. S.D.

AccuBond® Long Range ABLR			190gr. Spitzer	2.810"	0	.597	0.286	
Custom Competition®			190gr. HPBT	2.810"	0	.530	0.286	
CASE TYPE:	Hornady			PRIMER TYPE			WLRM	
CASE HOLDS:	61.5 Gr. WATER		BARREL Length/Make			24" Pac-Nor		
			BARREL Twist			1-10"		
POWDER POWDER CHG.			MUZZLE VEL.			LOAD DENSITY		
TYPE	GRS.			F.P.S.			(VOLUME)	
IMR 4831	58.0	MAX.	2759			**	1	01%
	56.0		2641				! !	97%
	54.0	*	2524				9	94%
Hybrid 100V	56.0	MAX.	2771				9	94%
	54.0	*	2671				9	91%
	52.0		2571				;	87%
RL19	61.0	MAX.	2822			**	1	08%
Most Accurate	59.0		2716			**	1	04%
Powder Tested	57.0	*	2611			**	1	01%
Hunter	61.0	MAX.	2824			**	1	02%
	59.0	*	2753				9	99%
	57.0		2681				9	96%

2.840"

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the

condition of the finearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

^{* =} Most accurate load tested

^{** =} Compressed load