Cartridge

300 Win Mag - 190 grain

NOSLER

Version 9.0



300 Win Mag - 190 grain MAXIMUM SAAMI O.A.C.L. TESTED O A C I 3.340"

R C SD ABLR 190gr. Spitzer 3.330"

BARREL Length/Make

BARREL Twist

MUZZLE VEL.

F.P.S.

3.330"

AccuBond® Long Range 190gr. HPBT Nosler PRIMER TYPE

Custom Competition® CASE TYPE:

83.2 Gr. WATER

CASE HOLDS:

POWDER CHG. GRS.

POWDER TYPE 71.5 **RL19** MAX. 2921

69 5

67.5

MAGPRO 0.08

78.0

2830

2739

MAX. 2934 2854 76.0 2775 RL22 * MAX. 2935 73.5

71.5 2856 69.5 2776 **IMR 4350** 690

MAX 2941 67.0 2856 65.0 2770 **RL17** 68.0 Most Accurate 66.0

* MAX. 2948 2819 64.0 Powder Tested 2690 MAX. 2981 IMR 7828 SSC 76.0

74.0 2906 72.0 2832 MAX. 2987 79.0

2961

2877

3027

MAX. 3064

77.0 2924 75.0 2862 72.0 MAX. 3028 70.0 2951

H1000

Magnum

PP 4000-MR 68.0 2873 Norma MRP 77.0 MAX. 3044

75.0

86.0 84.0

73.0 *

82.0 2991 All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary * Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

30 Cal. (.308") 0.597 0.286 0.530 0.286 WLRM

24" H-S Prec.

1-10" (VOLUME)

LOAD DENSITY 93% 91% 88% 99% 97%

94% 96% 93% 91% 89% 86% 84%

85% 82% 80%

94% 92% 89% 100% ** 98% 95% 91% 89% 86%

102%

99%

96%

105%

102%

100%

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data." * = Most accurate load tested

^{** =} Compressed load