
CARTRIDGE

308 Marlin Express - 170 grain

Version 8.0

NOSGI UP FRONT



TESTED O.A.C.L. B.C.

308 Marlin Express - 170 grain MAXIMUM S.A.A.M.I. O.A.C.L. 2.600"

30 Cal. (.308")

Partition®				170gr. RN	2.380"		0.252	0.256	
CASE TYPE:	Hornady			PRIMER TYPE			Fed.	Fed. 210	
CASE HOLDS:	42.2 Gr. WATER		BARREL Length/Make			24" F	24" Pac-Nor		
				BARREL Twis	it		1-12	"	
POWDER	POWE	DER CHG.		MUZZLE VEL			LOAD	DENSITY	
TYPE	GRS.			F.P.S.			(VOL	UME)	
X-Terminator	36.5	MAX.	2430					88%	
	34.5		2312					83%	
	32.5	*	2187					78%	
A-2520	39.5	MAX.	2454					96%	
	37.5	*	2359					92%	
	35.5		2264					87%	
Varget	39.5	MAX.	2458				**	101%	
	37.5		2343					96%	
	35.5	*	2220					91%	
IMR 8208 XBR	38.0	MAX.	2462					99%	
Most Accurate	36.0	*	2340					94%	
Powder Tested	34.0		2213					89%	
IMR 4064	39.5	MAX.	2473				**	103%	
	37.5		2346					98%	
	35.5	*	2219					92%	
RL15	40.5	MAX.	2486					100%	
	38.5		2365					95%	
	36.5	*	2244					90%	

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.

^{* =} Most accurate load tested

^{** =} Compressed load