
CARTRIDGE

330 Dakota - 225 grain

Version 8.0

NOSIGIF UP FRONT



330 Dakota - 225 grain

MAXIMUM O.A.C.L. 3.320"

338 Cal. (.338")

99%

| | TO A CO | 5.5_0 | | | | | | ٥.٠. |
|---------------|----------------|----------|--------------------|----------------|--|-----------|----------|---------|
| AccuBond® | | | | 225gr. Spitzer | | 0. | 550 | 0.281 |
| Partition® | | | | 225gr. Spitzer | | 0. | 454 | 0.281 |
| CASE TYPE: | Dakota | | | PRIMER TYPE | | | Fed 215 | |
| CASE HOLDS: | 85.7 Gr. WATER | | BARREL Length/Make | | | 26" Lilja | | |
| | | | | BARREL Twist | | | 1-10" | |
| POWDER | POWD | ER CHG. | | MUZZLE VEL. | | | LOAD | DENSITY |
| TYPE | GRS. | | | F.P.S. | | | (VOLUME) | |
| H4831SC | 79.0 | MAX. 2 | 842 | | | | 9 | 96% |
| | 77.0 | * 2 | 786 | | | | 9 | 94% |
| | 75.0 | 2 | 715 | | | | 9 | 91% |
| Viht N160 | 77.5 | MAX. 2 | 862 | | | | 1 | 00% |
| | 75.5 | * 2 | 798 | | | | 9 | 98% |
| | 73.5 | 2 | 725 | | | | | 95% |
| IMR 4350 | 76.5 | * MAX. 2 | 887 | | | | 9 | 94% |
| Most Accurate | 74.5 | 2 | 832 | | | | 9 | 92% |
| Powder Tested | 72.5 | 2 | 769 | | | | | 90% |
| RL19 | 82.0 | MAX. 2 | 894 | | | ** | 1 | 04% |
| | 80.0 | 2 | 875 | | | ** | 1 | 01% |
| | | | | | | | | |

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, inc. be liable for any damages resulting from the use of this data."

2817

78.0 *

^{* =} Most accurate load tested

^{** =} Compressed load