Cartridge

350 Rem Mag - 225 grain

Version 9.0

92%

NOSLER



350 Rem Mag - 22	35 Cal. (.358")				
MAXIMUM SAAMI O.A.C.I	-•	2.800"	TESTED O.A.C.L.	B.C.	S.D.
Partition®	PT	225gr. Spitzer	2.780"	0.421	0.251

CASE TYPE:	Remington		PRIMER TYPE		CCI 250	
CASE HOLDS:	62.6	Gr. WATER	BARREL Length/Make		22" Lilja	
			BARREL Twist		1-16"	
POWDER POWDER CHG.		MUZZLE VEL.		LOAD DENSITY		
TYPE	GRS.		F.P.S.		(VOLUME)	
H380	60.5	MAX. 2528		**	102%	
	58.5	2443			98%	
	56.5	* 2358			95%	
RL7	47.0	MAX. 2570			82%	
	45.0	2460			78%	
	43.0	* 2350			75%	
H4895	56.0	* MAX. 2592			98%	
	54.0	2497			95%	
	52.0	2402			91%	
AA 2015	53.0	* MAX. 2621			96%	
	51.0	2508			93%	
	49.0	2394			89%	
IMR 4320	60.0	MAX. 2640		**	104%	
Most Accurate	58.0	2550			101%	
Powder Tested	56.0	* 2460			97%	
W748	59.0	* MAX. 2700			98%	
	57.0	2618			95%	

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

2535

55.0

^{*}Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.*

^{* =} Most accurate load tested

^{** =} Compressed load