
Cartridge

416 Rem Mag - 400 grain

Version 9.0

100%





416 Rem Mag - 400 grain 416 Cal. (.416") MAXIMUM SAAMI O.A.C.L. 3.600" TESTED O.A.C.L. B.C. S.D.

400gr. Spitzer 3.590" 0.390 0.330 Partition® Solid® 400gr. Solid 3.600" 0.289 0.330

TVDF	GRS	EDC	(VOLUME)
POWDER POWDER CHG.		MUZZLE VEL.	LOAD DENSITY
		BARREL Twist	1-14"
CASE HOLDS:	80.0 Gr. WATER	BARREL Length/Make	24" H-S Prec.
CASE TYPE:	Norma	PRIMER TYPE	WLRM

TYPE	GRS.	MUZZLE VEL. F.P.S.		(VOLUME)
AA 2015	71.0 MAX. 2346		**	101%
	69.0 * 2302			98%
	67.0 2258			95%
IMR 8208 XBR	72.0 MAX. 2365			99%
	70.0 * 2306			96%
	68.0 2246			93%
W748	80.0 * MAX. 2389		**	104%
	78.0 2326		**	102%

70120.5	, 1.0	23 10				0.70
	69.0 *	2302			9	98%
	67.0	2258			9	95%
IMR 8208 XBR	72.0 MAX.	2365			9	99%
	70.0 *	2306			9	96%
	68.0	2246			9	93%
W748	80.0 * MAX.	2389		**	1	04%
	78.0	2326		**	1	102%
	76.0	2263			9	99%
Big Game	83.0 * MAX.	2394		**	1	06%
	81.0	2358		**	1	103%
	79.0	2321		**	1	101%
IMR 4064	77.5 * MAX.	2436		**	1	107%
Most Accurate	75.5	2383		**	1	104%
Powder Tested	73.5	2330		**	1	102%
Varget	79.0 * MAX.	2468		**	1	107%
	77.0	2417		**	1	104%
	75.0	2365		**	1	101%
RL15	81.0 MAX.	2503		**	1	105%
	79.0 *	2453		**	1	103%

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary

2404

77.0

^{*} Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.'

^{* =} Most accurate load tested

⁼ Compressed load