Cartridge

458 Win Mag - 500 grain

Version 9.0

		i L. I			532	0.513 			0.481
458 Win M						458	Ca	al. (.	458")
MAXIMUM S	AAMI	O.A.C.L		3.340"		TESTED O.A.C.L.	В	.C.	S.D.
Partition®			PT	500gr. PPT		3.320"	0	.389	0.341
Solid®			SD	500gr. Solio	k	3.320"	0	.246	0.341
CASE TYPE:	Winchester			PRIMER TYPE				WLRM	
CASE HOLDS: 64.2 Gr. WATER			BARREL Length/Make				24" Pac-Nor		
				BARREL Tw				1-14"	
POWDER		DER CHG.		MUZZLE VE	L.				DENSITY
ТҮРЕ	GRS.			F.P.S.				(VOL	
RL7	58.0	MAX.							98%
	56.0	~	1920						95%
	54.0		1854				**		91%
W748	71.0	MAX.					**		15% 12%
	69.0 67.0	*	1981 1935				**		09%
X-Terminator		MAX.					**		09%
x-rerminator	04.0	IVIAA.	2052				**		0270
	620	*	1070						000%
	62.0	*	1979						99% 96%
TAC	60.0		1926				**		96%
ТАС	60.0 68.0		1926 2086				**	1	96% 08%
ТАС	60.0 68.0 66.0	MAX.	1926 2086 2038					1	96% 08% 04%
	60.0 68.0 66.0 64.0	MAX. *	1926 2086 2038 1990				**	1 1 1	96% 08% 04% 01%
TAC H335 Most Accurate	60.0 68.0 66.0 64.0	MAX. * * MAX.	1926 2086 2038 1990				**	1 1 1 1	96% 08% 04%

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary ^a Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In o event shall Nosler, Inc. be liable for any damages resulting from the use of this data.

* = Most accurate load tested

** = Compressed load