Cartridge


7mm Rem SA Ultra Mag - 120 grain

7mm Rom SA Illtra Mag - 120 grain

Version 9.0

91%

NOSLER



111 9 F	a Ollic		ag - 120 gi	alli	/ III	шц (•	20 4)
MAXIMUM SAAMI O.A.C.L.			2.825"	TESTED O.A.C.	.L. E	3.C.	S.D.
Ballistic Tip®			120gr. Spitzer	2.800"	C	.417	0.213
CASE TYPE: Nosler			PRIMER TYPE			Rem 9 1/2M	
69.2 Gr. WATER			BARREL Length/Make			24" Wiseman	
			BARREL Twist			1-9 1/	2"
POWDER POWDER CHG.			MUZZLE VEL.			LOAD DENSITY	
GRS.			F.P.S.			(VOLU	JME)
65.5	MAX.	3355			**	1	03%
63.5		3240				1	00%
61.5	*	3125				9	97%
64.0	MAX.	3412				٥	99%
62.0		3308				٥	96%
60.0		3203				٥	93%
64.5	MAX.	3428				9	97%
62.5		3339				Ç	94%
	Nosle 69.2 POWD GRS. 65.5 63.5 61.5 64.0 62.0 60.0 64.5	Nosler 69.2 Gr. WAT POWDER CHG. GRS. 65.5 MAX. 63.5 61.5 * 64.0 MAX. 62.0 * 60.0 64.5 MAX.	Nosler 69.2 Gr. WATER POWDER CHG. GRS. 65.5 MAX. 3355 63.5 3240 61.5 * 3125 64.0 MAX. 3412 62.0 * 3308 60.0 3203 64.5 MAX. 3428	Nosler	Nosler	Nosler	Nosler

3250 All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

60.5 *

[&]quot;Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data. In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

Most accurate load tested

^{** =} Compressed load