# **Cartridge**

### 7mm STW - 120 grain

## Version 9.0





MAXIMUM SAAMI O.A.C	.L.
D III .: T: @	пт

				2.389 		-
7mm ST	W - 120 gr	ain		7r	nm (.:	284")
MAXIMUM S	SAAMI O.A.C.L.		3.600"	TESTED O.A.C.L.	B.C.	S.D.
Ballistic Tip®		BT	120gr. Spitzer	3.600"	0.417	0.213
CASE TYPE:	Nosler		PRIMER TYPE		Fed 2	15

**BARREL Twist** 

MUZZLE VEL.

F.P.S.

Ballistic Tip®		RI
CASE TYPE:	Nosler	
ASE HOLDS	02 6 Gr WΔ	TER

ballistic Tip		DI	120
CASE TYPE:	Nosler		PRIM
CASE HOLDS:	92.6	Gr. WATER	BAR

Ballistic Tip®			BT
CASE TYPE:	Nosler		
CASE HOLDS:	92.6	Gr WAT	FR

Tip®		BT	120gr. Spitzer	3.60
PE:	Nosler		PRIMER TYPE	
LDS:	92.6	Gr. WATER	BARREL Length/N	/lake

Nosle	r
92.6	Gr. WATER

CASE TYPE:	Nosler	'
CASE HOLDS:	92.6	Gr. WATER

CASE TYPE:	Nosler	
CASE HOLDS:	92.6	Gr. WATER

CASE TYPE:	Nosler	
CASE HOLDS:	92.6	Gr. WATER

- POWDER CHG.
- **POWDER TYPE** GRS.
- H4831 78.5 MAX. 3428
- 76.5

N165

**RL19** 

N160

**IMR 4350** 

Most Accurate

- 3324 74.5
- 3220 MAX. 3484 80.0
- 78.0
- 3389 76.0 3295 77.5 MAX. 3509
- 75.5 3403 73.5
- 3296 76.5 74.5
- MAX. 3535 3439 72.5 3342
- 76.0 MAX. 3554 74.0 3453 72.0
- Powder Tested **IMR 4831** 77.5 MAX. 3578 75.5 3463 73.5 3348
  - **IMR 7828** 81.5 MAX. 3580 79.5 3477 77.5 3374 RL22 80.5 MAX. 3618

78.5

76.5

Magnum 92.0 MAX. 3629 90.0 3547 88.0 3465

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

3511

3405

- - - 26" Lilja 1-9"
      - LOAD DENSITY (VOLUME) 88%
      - 86% 84% 96%
    - 94% 91% 91% 89% 86%
    - 92% 89% 87% 88% 85% 83%
    - 90% 87% 85% 94% 91% 89%

94% 92%

90% 101%

99%

96%

- All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data
- \* = Most accurate load tested
- \*\* = Compressed load