Cartridge


8mm Rem Mag - 200 grain

Version 9.0

87%

NO5LER®

8mm Rem Mag - 200 grain



MAXIMUM SAAMI O.A.C.L.				3.600"	TESTED O.A.C.L.	B.C.	S.D.	
AccuBond® AB			AB	200gr. Spitzer	3.580"	0.450	0.274	
Custom Competition®			CC	200gr. HPBT	3.600"	0.520	0.274	
Partition® PT			PT	200gr. Spitzer	3.550"	0.426	0.274	
CASE TYPE:	Remington			PRIMER TYPE		Fed 2	Fed 215	
CASE HOLDS:	91.1 Gr. WATER			BARREL Length/Make		24" V	24" Wiseman	
				BARREL Twist		1-10'	1-10"	
POWDER POWDER CHG.				MUZZLE VEL.		LOAD	DENSITY	
TYPE	GRS.			F.P.S.		(VOL	UME)	
IMR 7828	83.5	MAX.	2930				98%	
	81.5		2850				95%	
	79.5	*	2770				93%	
RL22	80.5	* MAX.	2950				96%	
Most Accurate	78.5		2850				94%	
Powder Tested	76.5		2750				91%	
N165	79.0	* MAX.	2980				96%	
	77.0		2924				94%	
	75.0		2867				91%	
IMR 4350	74.0	* MAX.	3030				87%	
	72.0		2960				85%	
	70.0		2890				82%	
IMR 4831	78.0	MAX.	3050				92%	
	76.0		2980				89%	

All cartridge measurements are SAAM I maximum and due to variations from manufacturers actual measurements may vary "Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the

2910

74.0 *

condition of the finearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data."

^{* =} Most accurate load tested

^{** =} Compressed load